Extending a Roof Downward Over a Bumpout

Reference Number: **KB-00096**Last Modified: **October 2, 2024**

This article also applies to the following legacy products:

Pro | Architectural | Suite

QUESTION

How do I extend a roof down over a bumpout without changing the plate height of the main walls?



ANSWER

You can specify a single roof plane to extend downward over an exterior bumpout


using the "Extend Slope Downward" setting located on the Roof panel of the **Wall Specification** dialog.

Wall Specification			
General	Roof Options		
Structure		O Hip Wall	O High Shed/Gable Wall
Roof			
Foundation		 Full Gable Wall 	○ Knee Wall
Wall Types		O Dutch Gable Wall	Extend Slope Downward
Wall Cap			75
Wall Covering	Roof Cuts Wall at Bottom		
Rail Style		✓ Include Frieze	
		<u> </u>	
Newels/Balusters	Include Automatic End Truss Above		
Rails		Include Automatic	c Liid iidss Above

It's important to be aware that for this setting to work correctly, the following requirements must be met:

- The wall that is marked as "Extend Slope Downward" must connect to two perpendicular walls that are set as "Full Gable Walls".
- The wall marked as "Extend Slope Downward" must be parallel to at least one wall up the roof slope, of which will determine the pitch and height of the roof.
- If there are parallel walls on both sides of the wall marked as "Extend Slope Downward", and they are up the roof slope, they must be collinear to each other.

Please see the image below for reference.



If one or more of these requirements are not met, you will be prompted with one of the following messages, along with the program circling the problem wall or area. Click **OK** on the message and define the roof directives in the walls to meet the requirements.

- "#272009050 A wall designated "extend slope downward" may not also be designated as a "full gable wall" or "high shed wall"."
- "#272009051 / #272009052 A wall designated "extend slope downward" must connect at each end to two perpendicular walls that extend from it in the up roof slope direction. Each of these walls must be designated a "full gable wall"."
- "#272009053 If a wall designated "extend slope downward" has a parallel wall positioned up the roof slope on both sides of it, these walls must be collinear."

• "#272009054 - A wall designated "extend slope downward" must have a parallel wall up the roof slope that defines the roof pitch and height."



(https://chieftalk.chiefarchitect.com/)

(/blog/)



(https://www.facebook.com/ChiefArchitect)



(https://www.youtube.com/user/ChiefArchitectInc)



(https://www.instagram.com/chiefarchitect/)



(https://www.houzz.com/pro/chiefarchitect/)



(https://www.pinterest.com/chiefarchitect/)

208-292-3400 (tel:+1-208-292-3400)

© 2000–2025 Chief Architect, Inc.

Terms of Use (/company/terms.html)

Privacy Policy (/company/privacy.html)